



Description: **LOW TEMP USDA PVC PLASTIC STRIP, MADE IN USA**

PRODUCT SPECIFICATIONS

SAVE-T PVC STRIP & SHEET QCP-8300 & QCP-8300S

Roll Size		
THICKNESS:	.040” to .250”	
WIDTH:	4” to 60”	
Material Description		
FINISH:	Double Polished	
COLOR:	Clear	
REINFORCEMENT:	Nylon Beacon - 210 denier	
Physical Properties		
Property	Result	ASTM
Hardness (15 sec. delay)	70 A Scale	D2240
Tensile Strength:	2200 PSI	D412
Ultimate Elongation:	400%	D412
Graves Tear:	220 PPI	D1004
100% Modulus:	1000 PSI	D412
Stiffness: (-20°F)	-	-
Brittleness Temp:	-55° F	D746
Operating Temp:	-30° F to 150° F	-
Specific Gravity:	1.20	D792
Density:	75 lbs. cu.ft.	C-177
Thermal Conductivity (K):	.73	C-177
Thermal Resistance (R):	1.37	C-177
UV Resistance:	YES	
Flammability Rating:	Select Material Compliant with CA State Fire Marshal	

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

QE QUALITY ENGINEER

9400 NW 12 STREET
DORAL, FL 33172

Web-Site: www.qequality.com

Phone: 305-599-2222

Fax: 305-593-0069

E-mail: qequality@qequality.com